



Source One N.A. LLC - SONA Filtration

701 Green Valley Road

Suite 100 - 1007

Greensboro, NC 27408

888.650.3320

MP FILTRI MF0202A25HB HYDRAULIC FILTER REPLACEMENT

SPECIFICATIONS:



O.D.	1.65"
I.D. Top	0.90"
I.D. Bottom	24.7 PSID Bypass Valve
Length Overall	6.69"
Construction Type	Optimized Microglass, Single Open End with bypass valve
Efficiency	B26.6=1000 per ISO 16889, 20 micron; B20.7=200
Gasket Material	Viton
Wire Support	Yes
Max Operating Pressure	145 PSID Collapse
Max Temp	148 Degrees F
Weight Each	1.25
Carton Qty	1
Condition	New

Direct replacement for **MP Filtri MF0202A25HB** hydraulic filter element in form, fit, and function. **Made in America** with ISO 9001:2015 compliant manufacturing for assured quality. Optimized microglass media is used for fine filtration, long life, and high dirt-holding capacity.

- 1.65" OD x 0.90" ID Top x 6.69" Length overall
- 20 micron; B20.7=200, B26.6=1000 per ISO 16889
 - 145 PSID Collapse
- Scroll down for additional specs

SKU: S99-MF0202A25HB

Our filtration products are not suitable for Aviation applications. Registered Trademarks of indicated manufacturers are the property of those manufacturers and it is not our intent to imply that Source One N.A. is authorized or licensed to manufacture products under such manufacturer's name or trademark.

November 17, 2025

